

GNSS Reference Receiver



- 452-Channel Vanguard Technology with Universal Tracking Channels
- Superior signal tracking across the entire GNSS spectrum
- High-precision code and carrier phase measurements up to 100 Hz
- Built-in *Bluetooth*® and Wi-Fi connectivity
- Integrated web interface with advanced receiver management features
- 32GB SDHC storage support

Leading Reference Station Receiver

Using the Topcon premium Vanguard and Universal Tracking Channel technologies, the NET-G5 GNSS receiver incorporates 452 channels capable of tracking multi-frequency signals from all GNSS constellations including GPS, GLONASS, SBAS, QZSS, Galileo and BeiDou. This comprehensive support includes current and modernized signals across the full GNSS spectrum, including multiple L-band signals. The integrated Vanguard Technology has also demonstrated successful tracking and demodulation of advanced QZSS signal structures such as the LEX signal in E6.

The NET-G5 receiver offers a complete system connectivity solution by



allowing the receiver to be accessed via Ethernet, Wi-Fi, or Bluetooth® as well as by using standard serial or USB connections. The NET-G5 can also serve as a USB Host and provides a new web-based user interface that offers flexible configuration options and portability. The USB Host feature allows the user to connect a USB memory stick or USB Mass Storage Device (UMS) to the NET-G5 receiver. The UMS provides a simple solution for transferring raw data files from the receiver's SD card, or extending the NET-G5 with a semi-permanent high-capacity storage option. The NET-G5 supports flash-based UMS devices as well as hard drive-based UMS devices.

Premium positioning technology, extended communication support, advanced web-server capability, longer operating time, and high-reliability put the NET-G5 receiver a step ahead of the competition. When paired with one of the industry-leading Topcon geodetic antennas (CR-G5 and PN-A5), the NET-G5 receiver provides the ultimate GNSS networking and infrastructure solution available in the market today.

SPECIFICATIONS

GNSS

Number of Channels	452-Channel Vanguard Technology with Universal Tracking Channels
Signals Tracked	GPS, GLONASS, QZSS, SBAS, Galileo, L-Band and BeiDou (BDS)
Antenna Type	External – Geodetic full wave CR-G5 or PN-A5 antenna

Accuracy

RTK	H: 10 mm+1 ppm; V: 15 mm+1 ppm
Post processed Static	H: 3 mm+0.5 ppm; V: 5 mm+0.5 ppm

Data and Memory

Memory	Removable SD/SDHC memory card up to 32 GB and USB Host support for external USB mass storage devices
Data Update/Output Rate	1Hz - 100 Hz selectable
Data Output Format	TPS, RTCM SC104 v2.x and 3.x, CMR, CMR+, BINEX, RINEX
ASCII Output	NMEA 0183 version 2.1, 2.2, 2.3, 3.0 and 3.01

Communications

Cellular Communications	Integrated GSM; GSM Quad-band, CDMA2000, UMTS/HSPA+
I/O Communications	Class 2 Bluetooth® v2.0 + EDR WiFi 3 x RS-232 serial ports USB Host and Device supporting OTG functionality Ethernet (PoE Class 3)
NETRIP	Client, Caster, and Server functionality
TCP/IP and FTP	Multiple address ports
Web User Interface	Secure device access and configuration via Ethernet and Wi-Fi connectivity

Physical Characteristics

Status Indicators	8 LEDs Topcon MINTER
User Interface	Multi-function power button supporting data logging and factory reset operations
Dimensions (w x d x h)	5.9 x 7.9 x 2.4 in. (150 x 200 x 60 mm)
Weight	Less than 2 kg

Power

External Power Input	Nominal 12 VDC (external power input range 9V - 28VDC)
Power Consumption	Less than 5.0 W (typical)
Power Ports	2 x Power ports (1 primary and 1 backup) plus Class 3 PoE

Environmental

Operating Temperature	-40°C to 80°C with external power / -30°C to 65°C with integrated batteries
Dust and Water Protection	IP67
Humidity	100% condensing
Drop	2 meter drop to concrete surface, IEC 60068-2-29, IEC 60068-2-27
Vibration	Compliance with MIL-STD 810G, Method 514.6, Category 4
Shock	Method 516.6 (40 g RMS)

For more specification information: topconpositioning.com/net-g5



7400 National Drive • Livermore • CA 94550
(925) 245-8300

Specifications subject to change without notice. ©2014 Topcon Corporation
All rights reserved. P/N: 7010-2145 A TF 9/14

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Topcon is under license. Other trademarks and trade names are those of their respective owners.

Your local Authorized Topcon dealer is: